



Specification:
 Contact Resistance: 50m Ohm Max.
 Insulation Resistance: 100M Ohm Min.
 Voltage - Max:40V Maximum
 Current - Max:1.5A Maximum.
 Dielectric Withstanding Voltage:
 100V AC for 1 Minute.
 Durability (Life Test): 1000 Cycles
 Unmating Force:4.9 Newton TO 39 Newton Maximum.

1394A-SR2M-04-LF
 LEADFREE

RoHS Compliant

NO.	NAME	MATERIAL	FINISH	REMARK	Q'TY
1	HOUSING	NYLON PA9T G.F	BLACK		1
2	PIN TERM.	PHOS. BRONZE t:0.25mm	GOLD-TIN PLATED	NI:40~60u',TIN:120u', GOLD:30u'	4
3	FRONT SHELL	STEEL t:0.5mm	NICKEL PLATED	NI:80~120u'	1
4	REAR SHELL	PHOS. BRONZE t:0.2mm	NICKEL PLATED	NI:80~120u'	1

MORETHANALL
 CONNECTORS
 ASSEMBLIES

焯倫股份有限公司

PART NO. 1394A-SR2M-04		CHECKED BY CY		TOLERANCES ARE .X ± 0.2 .XX ± .XXX ± AWG	DESCRIP TION: IEEE 1394 AV CONNECTOR 4 PORT DIP 90° TYPE
DWG NO. 1394A-SR2M-04		DRAWING BY			
FILE NO.		PROJECTION		AREA	REVISIONS
UNIT / mm	SCALE 1:1			HK	DATE