



D-SHAPE TYPE A



CIRCUIT NO.

1.APPLICABLE CABLE: RECOMMENDED AWG30-26 * 8C
MAX AWG22 * 4C
OVERALL DI AMETER 6.7MAX.

ITEM	DESC.	MATERIAL	QUANTITY
9	HEAT SHRIN. TUBE	CROSS-LINKED POLYOLEFIN	1
8	COPPER FOIL TAPE	ELECTROLYSIS COPPER FOIL	1
7	BOTTOM COVER	PBT UL94V-0	1
6	TOP COVER	PBT UL94V-0	1
5	LOCK EJECTOR	PBT UL94V-0	1
4	BOTTOM SHELL	STEEL/UNDER:Cu PLATING, TOP:Ni PLATING	1
3	TOP SHELL	STEEL/UNDER:Cu PLATING, TOP:Ni PLATING	1
2	PLUG HSG COVER	PBT UL94V-0	2
1	PLUG HSG SUB ASSY	CONTACT:COPPER ALLOY UNDER ALL SURFACE:Ni PLATING TOP CONTACT AREA:Au PLATING SOLDERING AREA:Au FLASH HSG:PBT UL94V-0	1

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ± 0.30
.XX ±
.XXX ±
ANG ± 2°

PJECTION

照片框

ORDER INFORMATION

1394H-PA-08A-LF

SERIES | LEADFREE
8 PIN A TYPE
ASSEMBLY
MALE

DESCRIPTION: