



ELECTRICAL :	
IMPEDANCE :	75Ω
FREQUENCY :	0 TO 4.0 GHz
VSWR:	1.4 Max
RETURN LOSS:	≥ 15dB, 0.5 to 4 GHz

NO	DESCRIPTION	QTY	ITEM NO.	MATERIAL	PLATING
1	BODY 1	1	12-P225-7C-HI-ROHS	BRASS	SILVER
2	BODY 2	1	12-P225-7C-HI-ROHS	BRASS	GOLD 3-
3	DIELECTRIC 1	1	T-040273	TEFLON	-
4	DIELECTRIC 2	1	T-060398	TEFLON	-
5	CENTER PIN	1	12-P225-7C-HI-Be3	BERYLLIUM COOPER	GOLD 3-
6	PARTS	1	R-06002-ROHS	BRASS	GOLD 3-

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±

P PROJECTION



ORDER INFORMATION

1656-JR-75-LF  
SERIES | LEADFREE  
75 OHM  
DIP 90°  
JACK

DESCRIPTION: