



## SPECIFICATION

### A: MATERIAL:

1. HOUSING: PBT WITH 30% GLASS FIBER UL 94V-0
2. TERMINAL: COPPER ALLOY, TIN-PLATED

### B: CHARACTERISTICS:

1. RATING: 10A 250V~
2. INSULATION RESISTANCE: 100 MΩ MIN, AT 500V DC
3. ELECTRIC STRENGTH: AC 2,000V FOR ONE MINUTE

### C: APPROVALS:

UL, CSA, ENEC & CCC

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1:1

DATE

SIZE A4

X, ±  
.X ± 0.30  
.XX ± 0.20  
.XXX ± 0.10  
ANG ± 3°

PJECTION

照片框

ORDER INFORMATION

ACF-SQ4PE-03-LF  
SERIES | | | | LEADFREE  
| | | | 03WAY  
| | | | EAR  
| | | | PANEL  
FEMALE | | | | 4:4.8mm  
| | | | QUICK TAB

DESCRIPTION:

煜倫股份有限公司

www.morethanall.com