

Rating: 2.5A 250V AC
 Approvals: UL/CSA/VDE/NEMKO/CCC

PART No.	X	Y
ACR-PRPA2050-03	2.0	5.0
ACR-PRPA2030-03	2.0	3.0
ACR-PRPA2035-03	2.0	3.5
ACR-PRPA1550-03	1.5	5.0
ACR-PRPA1547-03	1.5	4.7
ACR-PRPA1530-03	1.5	3.0
ACR-PRPA1247-03	1.2	4.7

6		
5	Soldering PIN Brass Strip t=0.5mm Tin-Plated	2
4	Soldering PIN-TOP Brass Strip t=0.5mm Tin-Plated	1
3	Solid Contact PIN Brass Strip d=Ø2.36mm Ni-Plated	2
2	Solid Contact PIN Brass Strip d=Ø3.2mm Ni-Plated	1
1	Body Insulator PC Black Color	1

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ± 0.40


.X ± 0.30

.XX ± 0.10

.XXX ±

ANG ± 1°

PJECTION



ORDER INFORMATION

ACR-PRPAxxx-03-LF

SERIES | | | | LEADFREE
 | | | | 03 WAY
 | | | | 50:5.0mm DIP LENGTH
 MALE | | | | 20:2.0mm PNL THK
 DIP 90° | | | |
 PANEL FRONT

DESCRIPTION: