



Material:

1. Insulator: PBT+30% Glass Fiber(Meet UL94V-0).
2. Contact: Copper Alloy.
3. Contact Plated: Gold or Tin over Nickel Plated.

Specification:

1. Current Rating: 1 Amp.
2. Withstanding Voltage: AC 500V for 1 Minute.
3. Insulation Resistance: 1000MΩ Min. at DC 500V.
4. Contact Resistance: 15mΩ Max..
5. Operating Temperature: -40°C~+105°C.

No. of Contacts	Dim. A	Dim. B	Dim. C	Dim. D	Dim. E
10	23.00	18.00	10.16	11.43	19.72
14	28.08	23.08	15.24	16.51	24.80
16	60.62	25.62	17.78	19.05	27.34
20	35.70	30.70	22.86	24.13	32.42
24	40.78	35.78	27.94	29.21	37.50
26	43.32	38.32	30.48	31.75	40.04
30	48.40	43.40	35.56	36.83	45.12
34	53.48	48.48	40.64	41.91	50.20
40	61.10	56.10	48.26	49.53	57.82
50	73.80	68.80	60.96	62.23	70.52
60	86.50	81.50	73.66	74.93	83.22
64	91.58	86.58	78.74	80.01	88.30

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

PJECTION

照片框

ORDER INFORMATION

B-C3-xx-LF
SERIES | LEADFREE
10~64WAY
THREE TYPE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: 2.54mm IDC Box Header