



Recommended P.C.B Layout



60,64P 為三窗口

MATERIAL

Insulator: PBT+30%G.F UL94-V0  
Contact Pin : Brass

SPECIFICATION

Current Rate : 3 AMP  
Insulation Resistance : 5000MΩMin. at DC 500V  
Contact Resistance : 20mΩMax. at DC 100mA  
Dielectric Voltage : AC 500V for one minute  
Operation Temperature : -40°C to + 105°C

☆ Special Type

POLES	DIM A	DIM B	DIM C
☆ 6	12.66	10.26	5.08
6	15.20	12.80	5.08
☆ 8	15.20	12.80	7.62
8	17.78	15.48	7.62
10	20.30	18.10	10.16
12	22.84	20.64	12.70
14	25.38	23.18	15.24
16	27.92	25.72	17.78
20	33.00	30.80	22.86
24	38.08	35.88	27.94
26	40.62	38.42	30.48
30	45.70	43.50	35.56
34	50.80	48.58	40.64
40	58.40	56.20	48.26
44	63.48	61.28	53.34
50	71.10	68.90	60.96
56	78.72	76.52	68.58
60	83.80	81.60	73.66
64	88.88	86.68	78.74

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±  
.X ± 0.30  
.XX ± 0.20  
.XXX ±  
ANG ± 3°

P PROJECTION

照片框

ORDER INFORMATION

B-DG01-xx-LF  
SERIES | LEADFREE  
06-64WAY  
FULL GOLD 1u"  
DIP 180°

DESCRIPTION: BOX HEADER 2.54\*2.54mm, STRAIGHT TYPE