


RECOMMENDED PCB LAYOUT



SPECIFICATIONS:

Material:

Insulator: Hi-Temp Nylon 6T, rated UL-94V-0

Contacts: Brass

Contact Plating:

Gold Flash over Nickel underplate on contact area. Tin over copper underplate on solder tails.

Electrical:

Operating voltage: 250V AC max

Current rating: 1 Amp max

Contact resistance: 20 mohms max

Insulation resistance: 5,000 Mohms min

Dielectric withstanding voltage: 1,000 VAC / minute

Mechanical:

Mating durability: 500 cycles min

Temperature Rating:

Operating temperatures: -55 to +105

Recommended Soldering temp : 250 for 10 second

A = 2.54 X No. of positions / 2 + 7.6
 B = 2.54 X No. of positions / 2 + 5.08
 C = 2.54 X No. of spaces

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ±
 .X ±
 .XX ±
 .XXX ±
 ANG ±

PJECTION

照片框

ORDER INFORMATION

B-VS01-xx-LF
 SERIES | LEADFREE
 06-50WAY
 SEMI GOLD 1u"
 180°SMT

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: