



RECOMMENDED PCB LAYOUT
TOP VIEW(.XX±0.05)

PART NO.	DIM A	DIM B
BCS25-V24M1-03	2.4	4.30±0.2
BCS25-V30M1-03	3.0	4.90±0.2
BCS25-V35M1-03	3.5	5.40±0.2

性能:

额定电流: 2.0A

额定电压: 12V

耐电压: 500V

接触电阻: 30mΩ

绝缘电阻: 500MΩ

工作温度: -40℃~+85℃

塑件(材质): LCP

接触点(材质): 磷铜, 触点镀金3U"

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X.±

CHECKED BY GENIUS

.X±

UNIT/mm

SCALE 1:1

.XX±

DATE

.XXX±

ANG±

SIZE A4

PJECTION

照片框

ORDER INFORMATION

BCS25-VxxM1-03-LF

SERIES | LEADFREE
03 WAY
METAL FOOT
24:2.4mm HIGH
30:3.0mm HIGH
35:3.5mm HIGH
180°SMT

DESCRIPTION: BATTERY CONNECTORFPC PH2.5 3PIN 180度 SMT 有脚

煜倫股份有限公司

www.morethanall.com