








NOTE :

- 1.MATERIAL:
HOUSING:HIGH TEMP. THERMOPLASTIC,UL94V-0,COLOR BLACK
CONTACT:COPPER ALLOY,T=0.10
TAB:COPPER ALLOY,T=0.20
- 2.FINISH:
CONTACT:
SEE NOTE 5;
>1u" GOLD PLATING ON SOLDER TAILS;
NICKEL UNDERPLATING OVER ALL.
TAB:
MATTE TIN OVER ALL.
- 3.SOLDER HEAT RESISTANCE: REFLOW SOLDERING 260° FOR 5 SEC.
- 4.FOR REFLOW SOLDERING LEAD FREE PROCESS.



RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ± 0.25
.XX ± 0.15
.XXX ± 0.05
ANG ± 1°

PPOJECTION

照片框

ORDER INFORMATION

BCS25-W36EP2-06-LF

SERIES
LEADFREE
06 WAY
POST
EAR
HIGH 3.60mm
90°SMT

DESCRIPTION: