



TABLE

POS.	A	B	C	D
06	17.8	17.0	15.4	12.5
04	12.8	12.0	10.4	7.50

MATERIALS

HOUSING: HI-TEMP. PLASTIC (UL 94V-0), BLACK
 SOLDER PAD: COPPER ALLOY, TIN PLATING
 FORK: COPPER ALLOY, TIN PLATING
 TERMINAL: COPPER ALLOY, GOLD PLATED

SPECIFICATION

CURRENT RATING: 3 AMP MAX
 DIELECTRIC WITHSTANDING: 1000V AC FOR ONE MINUTE
 CONTACT RESISTANCE: 50m OHMS MAX
 INSULATION RESISTANCE: 1000M OHMS MIN AT DC 500V
 OPERATION TEMPERATURE: -40°C~+85°C

RoHS Compliant

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ± 0.40
 .X ± 0.30
 .XX ± 0.20
 .XXX ± 0.10
 ANG ±

PJECTION

照片框

ORDER INFORMATION

BCS25-W64EM2-xx-LF

SERIES | | | LEADFREE
 | | | 04.06 WAY
 | | | METAL FOOT
 | | | EAR
 | | | HIGH 6.45mm
 | | | 90°SMT

DESCRIPTION: BATTERY, 2.50mm PITCH, PCB MOUNT, R/A SMT, WITH PAD & FORK, FEMALE