



NOTE:

- 1.MATERIAL:
 - 1-1.CONTACT: BERYLLIUM COPPER.
 - 1-2.HOUSING: LCP.
- 2.PLATING:
 - 2-1.CONTACT: TIN/GOLD 30u".
- 3.SAFETY:
 - 3-1.RATED VOLTAGE: 200 VRMS AT SEA LEVEL.
 - 3-2.RATED CURRENT: 1.5 AMP.
 - 3-3.CONTACT RESISTANCE: 25 MILLIOHMS MAX.
 - 3-4.INSULATION RESISTANCE (IR): 10 MEGA-OHMS MIN.
 - 3-4.MATING CYCLES: REUSABLE 5000 TIMES WITHOUT DEGRADING ELECTRICAL CHARACTERISTICS.
 - 3-5.CONTACT FORCE: 200±30g.
- 4.HEAT TREATMENT:
 - 4-1.CONTACT: HV 360~410.

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

PJECTION

照片框

ORDER INFORMATION

BCS39-V23P-1X05-LF

SERIES POST HIGH 2.36mm 180°SMT
LEADFREE
05 WAY

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: 5PIN 電池座