



NOTE:

- 1.MATERIAL:
 - 1-1.CONTACT: PHOSPHOR BRONZE.
 - 1-2.GROUNDING TERMINAL: PHOSPHOR BRONZE.
 - 1-3.HOUSING: LCP(WHITE).
- 2.PLATING:
 - 2-1.CONTACT: GOLD FLASH/CONTACT GOLD 30u".
 - 2-1.GROUNDING TERMINAL: TIN 50u".
- 3.SAFETY:
 - 3-1.CURRENT RATING: CURRENT-1.5Adc/VOLTAGE-125Vdc , DURATION-THERMAL STABILITY.
 - 3-2.CONTACT FORCE: PRE-CONDITION-TERMINAL PUSH 3 CYCLES, SPEED-25.4mm/min.
 - 3-3.COMPRESSION VALUE: SPEED-25.4mm/min,DISTANCE-1mm.
 - 3-4.THERMAL SHOCK: -40° C/min~100° C/30min, AS A CYCLE,TOTAL 5 CYCLES.

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X. ±

CHECKED BY GENIUS

.X ±

UNIT / mm

SCALE 1 : 1

.XXX ±

DATE

ANG ±

SIZE A4

PJECTION

照片框

ORDER INFORMATION

BCS65-W71P-03-LF
SERIES | | | LEADFREE
| | | 03 WAY
| | | POST
| | | HIGH 7.1mm
| | | 90°SMT

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: 3PIN 充電座