



NO	DESCRIPTION	MATERIAL	FINISH	QTY
5	PIN	COPPER	TIN	1
4	PIN	COPPER	TIN	1
3	INSULATOR	PCM	NONE	1
2	BODY	ZINC ALLOY	NICKEL	1
1	CENTER CONTACT	PHOSPHOR BRONZE	GOLD	1

RECOMMENDED MOUNTING HOLE  
 MAXIMUM PANEL THICKNESS:5.5MM  
 RECOMMENDED MOUNTING TORQUE:  
 12 INCH-POUNDS MAX

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

X.±  
 .X±  
 .XX±  
 .XXX±  
 ANG±

PJECTION

照片框

ORDER INFORMATION

BNC-JD15XFM-50-LF  
 SERIES | | | | | LEADFREE  
 | | | | | 50 OHM  
 | | | | | FULL METAL  
 JACK | | | | | NON WASHER,NUT  
 | | | | | WIDE 15.8mm  
 | | | | | DIP 180°

DESCRIPTION: 50Ω BNC FEMALE PANEL MOUNT