



RECOMMENDED MOUNTING HOLE
 MAXIMUM PANEL THICKNESS: 5.5MM
 MATERIAL & FINISH

RECOMMENDED PC BOARD LAYOUT
 WITHOUT MOUNTING POSTS

- ① BODY: ZINC ALLOY, NICKEL PLATED
- ② INSULATOR: TEFLON
- ③ INSULATOR: TPX
- ④ CENTER CONTACT: PHOSPHOR BRONZE/TIN PLATED
- ⑤ CENTER CONTACT: PHOSPHOR BRONZE/GOLD PLATED

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±
 .X ±
 .XX ±
 .XXX ±
 ANG ±

PJECTION

照片框

ORDER INFORMATION

BNC-JR10XFM-75-LF
 SERIES | | | | LEADFREE
 | | | | 75 OHM
 | | | | FULL METAL
 JACK | | | | NON NUT/WASHER
 | | | | HIGH 10.94mm
 | | | | DIP 90°

DESCRIPTION: JACK, RIGHT ANGLE 75 OHM ,PCB BNC

煜倫股份有限公司

www.morethanall.com