



5	PIN	COPPER	TIN	1
4	PIN	COPPER	TIN	1
3	INSULATOR	PDM	NONE	1
2	BODY	ZINC ALLOY	NICKEL	1
1	CENTER CONTACT	PHOSPHOR BRONZE	GOLD	1
NO	DESCRIPTION	MATERIAL	FINISH	QTY

RECOMMENDED MOUNTING HOLE
 MAXIMUM PANEL THICKNESS: 5.5MM
 RECOMMENDED MOUNTING TORQUE:
 12 INCH-POUNDS MAX

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

DRAWING BY CY

X.±

CHECKED BY GENIUS

.X±

UNIT / mm

SCALE 1:1

.XX±

DATE

.XXX±

ANG±

煜倫股份有限公司

www.morethanall.com

SIZE A4

PJECTION

照片框

ORDER INFORMATION

BNC-JR15XFM-50-LF
 SERIES | | | | LEADFREE
 JACK | | | | 50 OHM
 DIP 90° | | | | FULL METAL
 HIGH 15.8mm | | | | NON NUT/WASHER

DESCRIPTION: BNC CONNECTOR, PCB/PANEL MOUNT JACKS