



RECOMMENDED MOUNTING HOLE  
 MAXIMUM PANEL THICKNESS:5.5MM  
 RECOMENDED MOUNTING TORQUE:  
 12 INCH-POUNDS MAX

NO	DESCRIPTION	MATERIAL	FINISH	QTY
6	SOLDER TAIL	BRASS WIRE	TIN LEAD	1
5	MOUNTING POST	BRASS	TIN LEAD	1
4	INSULATOR	POLYPROPYLENE (94 V-0)	NONE	1
3	HOUSING	NAN YA PBT(94 V-0)	NONE	1
2	BODY	ZINC ALLOY	NICKEL	1
1	CENTER CONTACT	PHOSPHOR BRONZE	GOLD	1

BNC-JR15Xxx-xx-LF  
 LEADFREE  
 50:50ohm  
 75:75ohm  
 WH:WHITE  
 BK:BLACK

RoHS Compliant



PART NO. BNC-JR15Xxx-xx		CHECKED BY CY	UNLESS OTHERWISE SPECIFIED TOLERANCES 0.5-5 =±0.2 6-30 =±0.4 30-120 =±0.6 120-315 =±1 315-1000 =±1.6 1000-2000 =±2.4	DESCRIPTION: BNC CONNECTOR, PCB/PANEL MOUNT JACKS		
DWG NO. BNC-JR15Xxx-xx						
FILE NO.		DRAWING BY	AREA	REVISIONS	HK	DATE
UNIT / mm	SCALE 1:1	PROJECTION				

焜倫股份有限公司