



RECOMMENDED  
CABLE STRIPPING DIM'S

13	NUT	ZINC	1	NICKEL PLATED
12	WASHER	IRON	1	NICKEL PLATED
11	NUT	ZINC	1	NICKEL PLATED
10	WASHER	IRON	1	NICKEL PLATED
9	RUBBER WASHER	RUBBER	1	RED
8	WASHER	ZINC	1	NICKEL PLATED
7	CENTER CONTACT	BRASS	1	GOLD PLATED
6	BODY	ZINC	1	NICKEL PLATED
5	GASKET	RUBBER	1	RED
4	INSULATOR	POM	1	NATURAL
3	INSULATOR	POM	1	NATURAL
2	WASHER	IRON	1	NICKEL PLATED
1	BODY	ZINC	1	NICKEL PLATED
ITEM	DESCRIPTION	MATERIAL	Q'TY	FINISHED

MODEL NO.	A	B	C	D	E	F	PART NO.
(RG58U)	Ø1.0	Ø4.5	Ø5.5	Ø7.5	Ø6.35	Ø5.5	BNC-JSPBNW-58
(RG59U)	Ø0.8	Ø5.5	Ø6.5	Ø7.5	Ø6.35	Ø6.5	BNC-JSPBNW-59
(RG6U)	Ø1.2	Ø6.0	Ø7.3	Ø8.5	Ø7.3	Ø7.3	BNC-JSPBNW-6

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

0.5-15 = ±0.15  
15-30 = ±0.30  
30-120 = ±0.60  
>120 = ±1.00  
ANGLES  
±3°

PJECTION

照片框

ORDER INFORMATION

BNC-JSPBNW-xx-LF  
SERIES | | | | LEADFREE  
58:RG58  
59:RG59  
6:RG6  
JACK  
SOLDER  
PANEL BACK | | | | WASHER  
NUT

DESCRIPTION: BNC MALE BULKHEAD CLAMP TYPE