



RECOMMENDED
CABLE STRIPPING DIM'S

1. CRIMPED FERRULE
HEX CRIMP SIZE .178"
2. CRIMPED CONTACT PIN
HEX CRIMP SIZE .068"

- NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
1. BRASS PER QQ-B-626
 2. BRASS PER QQ-B-613
 3. NICKEL PL.100 MIN. THICK OVER COPPER STRIKE
 4. NICKEL PL.200 MIN. THICK OVER COPPER STRIKE
 5. GOLD PL.1.5 MIN THICK OVER NICKEL PL.100 MIN.
THICK OVER COPPER STRIKE
 6. JIS H 3250, C 2700

11	FERRULE	NOTE6	1	NOTE3
10	SLEEVE	POM	1	NATURAL
9	CONTACT PIN	NOTE1	1	NOTE5
8	WASHER	IRON	1	NOTE3
7	SPRING	SK5	1	NOTE4
6	RETAINER RING	65Mn	1	NOTE3
5	GASKET	RUBBER	1	RED
4	INSULATOR	POM	1	NATURAL
3	INSULATOR	POM	1	NATURAL
2	BODY	ZINC	1	NOTE3
1	SHELL	ZINC	1	NOTE3
ITEM	DESCRIPTION	MATERIAL	Q'TY	FINISHED

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

0.5-15 = ±0.15
15-30 = ±0.30
30-120 = ±0.60
>120 = ±1.00

ANGLES
±5°

照片框

ORDER INFORMATION

BNC-PC-174-LF
SERIES | LEADFREE
RG 174
CRIMP
MALE

DESCRIPTION: BNC CRIMP PLUG 50 OHMS (FOR RG174U, CABLE)

煜倫股份有限公司

www.morethanall.com