


NOTES:FINISH (PLATING THICKNESS IN MICRO-INCHES)

- 1.BRASS PER QQ-B-626
- 2.BRASS PER QQ-B-613
- 3.NICKEL PL.100 MIN. THICK OVER COPPER STRIKE
- 4.NICKEL PL.200 MIN. THICK OVER COPPER STRIKE
- 5.GOLD PL.3 MIN THICK OVER NICKEL PL.100 MIN. THICK OVER COPPER STRIKE
- 6.JIS H 3250,C 2700

- 1.CRIMPED FERRULE  
HEX CRIMP SIZE .178"
- 2.CRIMPED CONTACT PIN  
HEX CRIMP SIZE .068"



RECOMMENDED  
CABLE STRIPPING DIM'S

10	FERRULE	NOTE6	1	NOTE3
9	CONTACT PIN	NOTE1	1	NOTE5
8	WASHER	NOTE2	1	NOTE3
7	SPRING	SK5	1	NOTE4
6	RETAINER RING	NOTE1	1	NOTE3
5	GASKET	RUBBER	1	RED
4	INSULATOR	POM	1	NATURAL
3	INSULATOR	POM	1	NATURAL
2	BODY	ZINC	1	NOTE3
1	SHELL	ZINC	1	NOTE3
ITEM	DESCRIPTION	MATERIAL	Q'TY	FINISHED

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

PJECTION

0.5-15 = ±0.15  
15-30 = ±0.30  
30-120 = ±0.60  
>120 = ±1.00  
ANGLES  
±3°

照片框

ORDER INFORMATION

BNC-PC-2.5C2V-LF  
SERIES | LEADFREE  
| 2.5C2V  
| CRIMP  
| MALE

DESCRIPTION: BNC CRIMP PLUG 75 OHMS (FOR 2.5C2V CABLE)

煜倫股份有限公司

www.morethanall.com