



1.MATERIALS :

- a. BODY : ZINC ALLOY,DIE CASTIN NICKEL PLATED.
  - b. CONTACT: BRASS NICKEL PLATED.
  - c. BRACKET: A.B.S .
  - d. INSULATOR: ENGINEER PLASTIC POM .
- 2.NOMIAL IMPEDENCE 50(75)OHMS.  
 3.FREQUENCY RANGE: 0-2 GHZ.  
 4.MAX PEAK VOLTAGE: 500V  
 5.DIELECTRIC STRENGTH WITHSTAND 1.5KV NNS.

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

**RoHS Compliant**

DRAWING BY CY

CHECKED BY GENIUS

UNIT/ mm SCALE 1:1

DATE

SIZE A4

UNLESS OTHERWISE SPECIFIED TOLERANCES

0.5-5	=±0.2
5-30	=±0.4
30-120	=±0.6
120-315	=±1
315-1000	=±1.6
1000-2000	=±2.4

P PROJECTION

照片框

**ORDER INFORMATION**

BNCA2-JRE2-50-LF

SERIES | | | LEADFREE  
 | | | 50 OHM  
 | | | EAR  
 | | | DIP 90°  
 | | | JACK

DESCRIPTION: BNC FEMALE R/A 1\*2 PORT