



**WIRING DIAGRAM**

DB25PM		BNC-F		DB25PM
14	CONDUCTOR	1	SPIRAL	
1	CONDUCTOR	2	SPIRAL	
2	CONDUCTOR	3	SPIRAL	
3	CONDUCTOR	4	SPIRAL	
4	CONDUCTOR	5	SPIRAL	
5	CONDUCTOR	6	SPIRAL	
20	CONDUCTOR	7	SPIRAL	
6	CONDUCTOR	8	SPIRAL	
7	CONDUCTOR	9	SPIRAL	
8	CONDUCTOR	10	SPIRAL	
9	CONDUCTOR	11	SPIRAL	
10	CONDUCTOR	12	SPIRAL	
11	CONDUCTOR	13	SPIRAL	
12	CONDUCTOR	14	SPIRAL	
13	CONDUCTOR	15	SPIRAL	
25	CONDUCTOR	16	SPIRAL	

D+15+16+17  
+18+19+21  
+22+24+25

PACKAGE: 1PCS/PE BAG

NO.	PART NO.	QTY	UNITS	DESCRIPTION
6	TUBE	32	PCS	SHRINK TUBE $\phi$ 2.0*10mm #BK
5	PVC	100	G	#BLACK 45P PVC
4	SCREW	2	PCS	D-E 30.5mm #4-40 BLACK
3	CONNECTOR	16	PCS	BNC-FEMALE
2	CONNECTOR	1	PCS	DB25P MALE #BK
1	CABLE	16	PCS	UL1185 24AWG 1C+S OD:2.8mm #BK L:380mm



PART NO. BNCDBX17-1625BK75-A32C

DWG NO. BNCDBX17-1625BK75-A32C

CHECKED BY CY

TOLERANCES ARE

DESCRIPTION: DB25PM/BNC-F\*16/0.32M

FILE NO.

DRAWING BY

.X ± 0.2  
.XX ±  
.XXX ±  
AWG

AREA	REVISIONS	HK	DATE

煜倫股份有限公司

UNIT / mm

SCALE 1:1

PROJECTION