



4	1SET	PCB SET (TRANSFORMER 1:1.26 *2, C1 1uF)	
3	1SET	PCB TYPE SHIELDED JACK, GOLD 50u"	GLASS FILLED POLYESTER UL 94V-0
2	1SET	PLASTIC SET (TOP, BOTTOM & SIDE COVER *2)	ABS UL 94V-0
1	2SET	BNC FEMALE SOLDER TYPE	NICKEL (100u" - 150u")
ITEM	Q'TY	DESCRIPTION	REMARK
PARTS LIST			

*Data Rates to 2.048 Mbps
 *Speed Ranges 2-8 Mbit/s
 *75 Ohm Dual Coax to 120 Ohm Twisted Pair
 *Bi-Directional Signal Conversion
 *No AC Power or Batteries Needed
 *Male Coax BNC Connectors Available

BNCRJ-FMBK-0288-LF
 BK BLACK LEADFREE

RoHS Compliant



PART NO. BNCRJ-FMBK-0288

DWG NO. BNCRJ-FMBK-0288

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

.X ± 0.2
.XX ±
.XXX ±
AWG

DESCRIPTION:				
AREA	REVISIONS	HK	DATE	

煜倫股份有限公司