



DESCRIPTION:

1. PVC MOLDED BLACK IN COLOR.
2. WIRE: UL1007 30AWG L 18MM BLACK IN COLOR.
3. SCREWS: M2.5 STEEL ZINC PLATED.
4. CONTACT: PHOSPHOR BRONZE.

ELECTRONIC TEST:

1. RATED VOLTAGE: 12V.
2. RATED CURRENT: 16A.
3. INSULATION RESISTANCE: 5000MΩ/1000V.
4. CONTACT RESISTANCE: 20mΩ
5. OPEN/SHORT INTERMITTE: 100%.

MECHANICAL:

1. TEMP. RANGE: -40°C~+105°C.
2. MAX SOLDERING: +250°C FOR 5SEC.

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

P PROJECTION

X.±
.X±
.XX±
.XXX±
ANG ±

照片框

ORDER INFORMATION

BNCTBN-EM-0202-LF

SERIES

LEADFREE

02 TO 02 WAY

MOLDING

MALE TO FEMALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: