



SPECIFICATION

Rating : 15A 250V AC 125V AC  
 Insulation resistance : DC 500V 100M ohm Min  
 Voltage breakdown : AC 1000V 1 minute

| 6   | NUT         | 2   | SPC      |               |
|-----|-------------|-----|----------|---------------|
| 5   | PANEL       | 1   | N66      |               |
| 4   | PANEL       | 1   | N66      |               |
| 3   | SHAFT       | 2   | BRASS    |               |
| 2   | BUSH        | 2   | SPC      | Ø3.6XØ10X1t   |
| 1   | KNOB        | 2   | N66      |               |
| NO. | DESCRIPTION | QTY | MATERIAL | SPECIFICATION |

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±  
 .X ±  
 .XX ±  
 .XXX ±  
 ANG ±

PJECTION

照片框

ORDER INFORMATION

BNN4A2-JSPA-41-LF

SERIES  
 LEADFREE  
 41.3mm LONG  
 PANEL FRONT  
 SOLDER  
 JACK

DESCRIPTION: