2.4±0.3

2.0±0.3

1.2±0.2

1.4±0.2

0.2

10.7±0.3

6.8±0.25

2.7±0.15

1.4 ±0.15

A — A'

B — B'

1.2±0.15

P.C BOARD DIP IN TERMINAL
MAT'L:PHOSPHOR BRONZE,BRASS

SUTTABLE TERMINAL:Ø1.2mm P.C.B
INSULATION O.D. 1.2-1.5mm
WIRE RANGE:AWG#24-28
CURRENT RATING:3A AC,DC
VOLTAGE RATING:250V AC,DC

Features and Benefits:

*Secures Wire to PC board before
 ware soldering
*Rapid and economical means
 of hand wiring PC boards

*Wire solders directly to PC board

*No additional contact resistance

TOLERANCES ARE

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm   SCALE 1:1

DATE

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

照片框

MMORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES
煜倫股份有限公司
www.morethanall.com

SIZE A4   PPOJECTION ⊕◁⊏

ORDER INFORMATION

BT-D12-24-LF

SERIES   LEADFREE
              24~28AWG
       PCB HOLE 1.2mm

DESCRIPTION: Stand Alone Board—In terminal