

*****CONSTRUCTION:**

1.CABLE: * UL2464 (2C/16#)+A OD:6.0mm BLACK JACKET.

*****CONNECTORS:**

2.CONNECTOR: * PITCH 5.0MM 6PIN TERMINAL BLOCKS Dinkle P/N TBH050-SW-06

3.TERMINAL: * TUBULAR TERMINAL (CET-1508-BK).

* WIRE SIZE:1.5mm²/16AWG LENGTH:10mm.

* INSULATED: NYLON(BLACK).

* COPPER WITH TIN PLATED.

4.TEST: * CT: 2 Ohm. IS: 5M Ohm.

5.PACKING: * PACK EACH CABLE IN A POLY BAG.

6.MATERIAL: * MATERIAL WITH RoHS GRADE.

PIN OUT

P1

1 — BLUE — T1

2 — BROWN — T2

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±


.X ±

.XX ±

.XXX ±

ANG ±

PPOJECTION



ORDER INFORMATION

CETTbHX21-100616R1-F80C-LF

SERIES

1006

16R1

F80C

LF

800mm LEADFREE

16 AWG FEMALE

ROUND CABLE

10mm TO 06 WAY

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: PITCH 5.0MM 6PIN TERMINAL BLOCKS TO TUBULAR TERMINAL