



NOTES:

1. MATERIAL:

- 1-1 Housing : Engineering plastic , LCP with G.F reinforced , black per UL 94V-0 rate.
- 1-2 Terminal : Phosphor Bronze , per JIS 5210 , 0.2t
- 1-3 Metal cover : SUS304 0.2t.

2. PLATING:

- 2-1 CONTACTS: 0.25 μ m (10 μ ") gold plating in contact area, and underplated with 1.27 μ m (50 μ ") min. Nickel over all.
- 2-2 Solder zone: 2.54 μ m (100 μ ") matte Tin, 1.27 μ m (50 μ ") min. Nickel underplating over all.

3. RoHS compliant products.

TOLERANCE: ±0.05
RECOMMENDED P.C. BOARD LAYOUT

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X, ±

CHECKED BY GENIUS

.X ±

UNIT / mm

SCALE 1 : 1

.XXX ±

DATE

ANG ±

煜倫股份有限公司

www.morethanall.com

SIZE A4

PJECTION

照片框

ORDER INFORMATION

CFA-PW41AE002L-24-LF
SERIES | | | | | LEADFREE
MALE | | | | | 24WAY
90°SMT | | | | | LOCK
POST TO POST 41.82mm | | | | | RVS
A TYPE EAR | | | | | STANDOFF 0.0mm

DESCRIPTION: Cfast host_4.3H 簡易型 (長腳吧)