



PULL OUT DIRECTION

TABLE A

D1042-FT-14	2.70	3.33	防水頭 12PIN (F) 端子半成品(Crimp PIN 14~18AWG)	MATTE TIN 80u"~100u"
D1042-FTN-14	2.70	3.33	防水頭 12PIN (F) 端子半成品(Crimp PIN 14~18AWG)	NICKEL 80u"~100u"
D1042-FT-12	3.35	4.40	防水頭 12PIN (F) 端子半成品(Crimp PIN 12~14AWG)	MATTE TIN 80u"~100u"
D1042-FTN-12	3.35	4.40	防水頭 12PIN (F) 端子半成品(Crimp PIN 12~14AWG)	NICKEL 80u"~100u"
P/N	L1	L2	TITLE	FINISH

1. MATERIAL :
 - 1-1. CONTACT : PHOSPHOR BRONZE
 - 1-2. SHELL : STAINLESS STEEL
2. FINISH :
 - 2-1. CONTACT : SEE TABLE A

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ± 0.20
.XX ± 0.10
.XXX ± 0.05
ANG ± 1°

PJECTION

照片框

ORDER INFORMATION

D1042-FTx-xx-LF

SERIES	LEADFREE
	12:12~14AWG 14:14~18AWG
BLANK:TIN PLATED	
N:NICKEL PLATED	
FEMALE TERMINAL	

DESCRIPTION: 防水頭 12PIN (F) 端子半成品(Crimp PIN)