


A-A



B-B

TABLE A

| | | | | |
|--------------|------|------|-------------------------------------|----------------------|
| D1042-MT-14 | 2.70 | 3.33 | 防水頭12PIN (M) 端子(Crimp PIN 14~18AWG) | MATTE TIN 80u"~100u" |
| D1042-MTN-14 | 2.70 | 3.33 | 防水頭12PIN (M) 端子(Crimp PIN 14~18AWG) | NICKEL 80u"~100u" |
| | | | | |
| D1042-MT-12 | 3.35 | 4.40 | 防水頭12PIN (M) 端子(Crimp PIN 12~14AWG) | MATTE TIN 80u"~100u" |
| D1042-MTN-12 | 3.35 | 4.40 | 防水頭12PIN (M) 端子(Crimp PIN 12~14AWG) | NICKEL 80u"~100u" |
| | | | | |
| P/N | L1 | L2 | TITLE | FINISH |

- MATERIAL :
 - CONTACT : PHOSPHOR BRONZE
- FINISH :
 - CONTACT : SEE TABLE A
UNDERPLATED : NICKEL 60u" ON OVER ALL

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

PJECTION

X, ±
.X ± 0.10
.XX ± 0.05
.XXX ± 0.03
ANG ± 1°

照片框

ORDER INFORMATION

D1042-MTx-xx-LF

SERIES | LEADFREE
12:12~14AWG
14:14~18AWG
BLANK:TIN PLATED
N:NICKEL PLATED
MALE TERMINAL

DESCRIPTION: