



| 7   | Contact Terminals | Brass    | Silver Ptd. | 5    |
|-----|-------------------|----------|-------------|------|
| 6   | 5P180 Housing     | ABS      |             | 1    |
| 5   | Shield Cover B    | Steel    | Nickel Ptd. | 1    |
| 4   | Shield Cover A    | Steel    | Nickel Ptd. | 1    |
| 3   | "O" Ring          | Brass    | Nickel Ptd. | 1    |
| 2   | Screw             | PA6      |             | 1    |
| 1   | Shell Cover       | PA6      |             | 1    |
| No. | Description       | Material | Treat       | Q'ty |

**Specifications**  
**rating :** 100V AC 1A MAX  
**contact resistance :** pins-30mΩ MAX; shell-50mΩ MAX  
**insulation resistance :** MIN 100 MEGΩ @500V DC  
**voltage withstand :** 250V AC R.M.S. for 1 minute

**RoHS Compliant**

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY  
 CHECKED BY GENIUS  
 UNIT / mm SCALE 1 : 1  
 DATE

X.±  
 .X±  
 .XX±  
 .XXX±  
 ANG ±

SIZE A4 PPROJECTION



ORDER INFORMATION

DA-PR-05-LF  
 SERIES | LEADFREE  
 90° | 05 WAY  
 MALE

DESCRIPTION: