



NUT

Panel Cut-Out

1. MATERIAL :
  - 1-1. HOUSING : PBT UL94V-0 ; COLOR : BLACK.
  - 1-2. CONTACT : BRASS
  - 1-3. SHELL : Zn ALLOY
  - 1-4. NUT : BRASS
2. FINISH :
  - 2-1. CONTACT : GOLD PLATED 10 MICRO INCHES MIN.  
UNDER PLATE : NICKEL
  - 2-2. NUT : NICKEL PLTAEED.
  - 2-3. SHELL : NICKEL PLTAEED.
3. ELECTRICAL SPECIFICATION :
  - 3-1. Rated current(40°C): 3A
  - 3-2. Rated Voltage : 60V
4. Environmental :
  - 4-1. Operation Temperature : -40°C~85°C

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±  
.X ± 0.20  
.XX ± 0.10  
.XXX ± 0.05  
ANG ± 1°

P PROJECTION

照片框

ORDER INFORMATION

DAMS-JS-12-LF  
SERIES | | LEADFREE  
| | 12 WAY  
| | SOLDER  
| | JACK

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: Dln Female receptacle screw locking rear mounting