



NUT

Panel Cut-Out

1. MATERIAL :
 - 1-1. HOUSING : NYLON UL94V-0 ; COLOR : BLACK
 - 1-2. CONTACT : PHOSPHOR BRONZE
 - 1-3. SHELL : Zn ALLOY
 - 1-4. NUT : BRASS
2. FINISH :
 - 2-1. CONTACT : GOLD FLASH MICRO INCHES MIN.
 - 2-2. NUT : NICKEL PLTAEED.
 - 2-3. SHELL : NICKEL PLTAEED.
3. ELECTRICAL SPECIFICATION :
 - 3-1. Rated current(40°C): 5A
 - 3-2. Rated Voltage : 250V
4. Environmental :
 - 4-1. Operation Temperature : -40°C~85°C

DAMS-JS-03	DAMS-JS-04	DAMS-JS-05	DAMS-JS-05B	DAMS-JS-06	DAMS-JS-07B	DAMS-JS-07	DAMS-JS-08

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ± 0.20
.XX ± 0.10
.XXX ± 0.05
ANG ± 1°

PJECTION



ORDER INFORMATION

DAMS-JS-xx-LF
SERIES | LEADFREE
| 03-08 WAY
| SOLDER
| JACK

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: Dln Female screw locking rear mounting Hex nuts