



No.	Description	Material	Treat	Q'ty
1	Shield Cover	Zn Alloy	Nickel Ptd.	1
2	Negative Contact	Copper	Nickel Ptd.	1
3	Terminals	Brass	Silver Ptd.	8
4	Screw Nut	Brass	Nickel Ptd.	1
5	Housing	PBT		1

#### Specifications

rating :

**100V AC 4A MAX**

contact resistance :

**pins-30m $\Omega$  MAX; shell-50m $\Omega$  MAX**

insulation resistance :

**MIN 100 MEG $\Omega$  @500V DC**

voltage withstand :

**250V AC R.M.S. for 1 minute**

Operating Temperature : **-55 $^\circ$ C~85 $^\circ$ C**

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X,  $\pm$   
.X  $\pm$   
.XX  $\pm$   
.XXX  $\pm$   
ANG  $\pm$

PJECTION

照片框

ORDER INFORMATION

DAMS-JS16-08-LF

SERIES | | LEADFREE  
| | 08 WAY  
| | 16.2 $\phi$   
SOLDER  
JACK

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: