



A-A SECTION

Specifications

rating :

100V AC 1A MAX

contact resistance :

pins-30mΩ MAX; shell-50mΩ MAX

insulation resistance :

MIN 100 MEGΩ @500V DC

voltage withstand :

250V AC R.M.S. for 1 minute

8	Contact Terminals	Brass	Silver Ptd.	6
7	6P Housing	ABS		1
6	Spring Ring	Steel	Nickel Ptd.	1
5	Setscrew	Steel	Nickel Ptd.	1
4	"T" Holder	Steel	Nickel Ptd.	1
3	Strain Boot	PVC		1
2	Screw Cap	Brass	Nickel Ptd.	1
1	Shell Cover	Brass	Nickel Ptd.	1
No.	Description	Material	Treat	Q'ty

DAMS-PA-06-LF
LEADFREE
RoHS Compliant

MORETHANALL
CONNECTORS
ASSEMBLIES

PART NO. DAMS-PA-06

DWG NO. DAMS-PA-06

FILE NO.

CHECKED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

X ±
.X ± 0.20
.XX ± 0.15
.XXX ± 0.05
ANG ± 1°

DESCRIPTION:	6P DIN CABLE PLUG SCREW LOCK		
AREA	REVISIONS	DATE	

焯倫股份有限公司

UNIT / mm

SCALE 1:1