



SECTION A-A

Specifications
rating :

250V AC 5A MAX

contact resistance :

pins-30mΩ MAX; shell-50mΩ MAX

insulation resistance :

MIN 100 MEGΩ @500V DC

Protection Degree : IP40

Cable Outlet : 3~6mm/6~8mm

No.	Description	Material	Treat	Q'ty
1	Housing Holder up	Zn Alloy	Nickel Ptd.	1
2	HousingHolder dn	Zn Alloy	Nickel Ptd.	1
3	Screw Cap	Brass	Nickel Ptd.	1
4	Strain Relief	TPR		1
5	Shell	PA6		1
6	Cable Holder	Steel	Nickel Ptd.	1
7	Screw	Steel	Nickel Ptd.	2
8	Housing	PA66		1
9	Terminals	Brass	Silver Ptd.	AS *TABLE A*

TABLE A

03	04	05	05B	06	07	08

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES
煜倫股份有限公司

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ± 0.20
.XX ± 0.10
.XXX ± 0.05
ANG ± 1°

P PROJECTION

照片框

ORDER INFORMATION

DAMS-PA65-xx-LF

SERIES | | | LEADFREE
03-08 WAY
LONG 65.25mm
ASSEMBLY
MALE

DESCRIPTION: M16 IP40 MALE CABLE CONNECTOR SCREW LOCKING

www.morethanall.com