

No.	Description	Material	Treat	Q'ty
1	shell Cover	PA6		1
2	Cable Screw	PA6		1
3	Screw	Brass	Nickel ptd.	1
4	"o" Ring	Brass	Nickel ptd.	1
5	Shield Cover A	Steel	Nickel ptd.	1
6	Shield Cover B	Steel		1
7	5P 180 Housing	ABS		1
8	Contact Terminals	Brass	Silver ptd.	5

### Specifications

rating: 100V AC 1A MAX  
 contact resistance:  
 pins-30mohm MAX; shell-50mohm MAX  
 insulation resistance:  
 MIN 100 MEGOHM @500V DC  
 voltage withstand:  
 250V AC R.M.S. for 1 minute

DAMS-PAR-05-LF

LEADFREE

RoHS Compliant

**MORETHANALL**  
 CONNECTORS  
 ASSEMBLIES

PART NO. DAMS-PAR-05

DWG NO. DAMS-PAR-05

FILE NO.


UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

.X ± 0.2  
 .XX ±  
 .XXX ±  
 AWG

DESCRIPTION:

AREA

REVISIONS

HK

DATE

焯倫股份有限公司