



A-A SECTION



6	Contact Terminals	Brass	Silver Ptd.	2
5	6P Housing	ABS		1
4	Strain Boot	PVC		1
3	Setscrew	Steel	Nickel Ptd.	1
2	"T" Cable Holder	Steel	Nickel Ptd.	1
1	Shell Cover	Zn Alloy	Nickel Ptd.	1
No.	Description	Material	Treat	Q'ty

**Specifications rating :**

**100V AC 1A MAX**

**contact resistance :**

**pins-30mΩ MAX; shell-50mΩ MAX**

**insulation resistance :**

**MIN 100 MEGΩ @500V DC**

**voltage withstand :**

**250V AC R.M.S. for 1 minute**

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES  
**煜倫股份有限公司**

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±

PPOJECTION

照片框

**ORDER INFORMATION**

DASM-JA-02-LF

SERIES | LEADFREE  
02 WAY  
ASSEMBLY  
FEMALE

DESCRIPTION:

[www.morethanall.com](http://www.morethanall.com)