



6	Contact Terminals	Brass	Silver Ptd.	AS TABLE
5	Housing	PA66		1
4	Strain Boot	PVC		1
3	Setscrew	Steel	Nickel Ptd.	1
2	"T" Cable Holder	Steel	Nickel Ptd.	1
1	Shell Cover	Zn Alloy	Nickel Ptd.	1
No.	Description	Material	Treat	Q'ty

DASM-JA-03	DASM-JA-04	DASM-JA-05	DASM-JA-05B	DASM-JA-06	DASM-JA-07	DASM-JA-08

Specifications rating :

- 100V AC 1A MAX
- contact resistance :
pins-30mΩ MAX; shell-50mΩ MAX
- insulation resistance :
MIN 100 MEGΩ @500V DC
- voltage withstand :
250V AC R.M.S. for 1 minute

RoHS Compliant

TOLERANCES ARE

照片框

ORDER INFORMATION

DASM-JA-xx-LF
 SERIES | LEADFREE
 | 03-08 WAY
 | ASSEMBLY
 | FEMALE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
 .X ± 0.30
 .XX ± 0.20
 .XXX ±
 ANG ±

PJECTION

DESCRIPTION: DIN JACK FOR CABLE