



7	Strain Boot	PVC		1
6	Terminals	Brass	Silver Ptd.	2
5	Housing	ABS		1
4	Setscrew	Steel	Nickel Ptd.	1
3	"T" Holder	Steel	Nickel Ptd.	1
2	Screw Cap	Zn Alloy	Nickel Ptd.	1
1	Shield Cover	Zn Alloy	Nickel Ptd.	1
No.	Description	Material	Treat	Q'ty

**Specifications  
rating :**

**100V AC 4A MAX**

**contact resistance :**

**pins-30mΩ MAX; shell-50mΩ MAX**

**insulation resistance :**

**MIN 100 MEGΩ @500V DC**

**voltage withstand :**

**250V AC R.M.S. for 1 minute**

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±

P PROJECTION

照片框

**ORDER INFORMATION**

DASM-PA-02-LF

SERIES | T LEADFREE  
| 02 WAY  
| ASSEMBLY  
MALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: