



7	Strain Boot			1
6	Terminals	Brass	Silver Ptd.	8
5	8P262 Housing	ABS		1
4	Setscrew	Steel	Nickel Ptd.	1
3	T Holder	Steel	Nickel Ptd.	1
2	YE-139X Cap	Zn Alloy	Nickel Ptd.	1
1	YE-139X Cover	Zn Alloy	Nickel Ptd.	1
No.	Description	Material	Treat	Q'ty

Specifications

rating :

100V AC 1A MAX

contact resistance :

pins-30mΩ MAX; shell-50mΩ MAX

insulation resistance :

MIN 100 MEGΩ @500V DC

voltage withstand :

250V AC R.M.S. for 1 minute

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

P PROJECTION

照片框

ORDER INFORMATION

DASM-PA-08B-LF

SERIES | LEADFREE
| 08 WAY B TYPE
ASSEMBLY
MALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: