


UNC #4-40 Hexscrew



HGC 50 M/F GENDER CHANGER
PIN OUT: 50Male 50Female

1	-----	1
2	-----	2
49	-----	49
50	-----	50
G	-----	G

Label: yellow color with black character
 One side: MINI GENDER CHANGER
 The other side: U.S.A. PATENT 5199906 GENDER CHANGER
 SPECIFICATION
 INSULATOR: PBT Glass fibre reinforced UL 94 V0
 CONTACT: Brass
 CONTACT PLATING: Gold plated over nickel
 SHELL: Tin plated shell
 CURRENT RATING: 3 AMP
 DIELECTRIC STRENGTH: 500V AC for one minute
 INSULATOR RESISTANCE: 500MΩ min at 500V DC
 TEMPERATURE: -55°C—+105°C

DBDB-ES-5050-LF
LEADFREE

RoHS Compliant



PART NO. DBDB-ES-5050	
DWG NO. DBDB-ES-5050	CHECKED BY CY
FILE NO.	DRAWING BY
UNIT / mm	SCALE 1:1

TOLERANCES ARE	X ± 0.2 .XX ± .XXX ± AWG
PROJECTION	

DESCRIPTION:				
AREA	REVISIONS	HK	DATE	

焯倫股份有限公司