



備注：  
 1.100% OPEN/SHORT TEST.  
 2.INSULATION RESISTANCE TEST : DC 5V/500KΩ.

PIN ASSIGNMENT

CN1	1	2	3	4	5	6	7	8	9	
CN2	1	2	3	4	5	6	7	8	9	10 N.C.

E	F-C3-10	1Set	PBT+G/F BLACK
D	4.75x11.8mm 螺絲	2Pcs	
C	DB-9M SOLDER TYPE	1Set	PBT+G/F, BLUE
B	DKA-N-0909	1Pcs	BLACK
A	FLAT-9C UL2651 P=1.27mm	1Pcs	28 AWG.
ITEM	DESCRIPTION	Q'TY	REMARK

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±  
 .X ±  
 .XX ±  
 .XXX ±  
 ANG ±

PJECTION

照片框

ORDER INFORMATION

DBF3-0910J1-E44C5-LF

SERIES | LEADFREE  
 445mm  
 MALE TO FEMALE  
 JACKSCREW  
 09 TO 10 WAY

DESCRIPTION: DB 9M CABLE L=445mm