



DBMIB-5B09-M1F-LF
LEADFREE
RoHS Compliant

Quality Requirement
Continuity: 2Ω
Insulation resistance: 10MΩ
Withstand voltage: 0.05Sec DC300V

Item	Name&Descriptions	Q'TY
1	28AWG(7/0.127 TA)*1P+28AWG(7/0.127 TA)*2C+A65 % OD:3.5±0.1mm	1PC
2	DB 9PIN MALE FRONT NI BACK TIN BLACK INSULATION TERMINAL PLATED GLOD FLASH SOLDER TYPE	1PC
3	DB 9PIN CONNECTOR INNERMOULD	G
4	DB 9PIN CONNECTOR OVERMOULD 40P/PVC BLACK	G
5	MICRO USB B CONNECTOR MALE SHELL PLATED GOLD TERMINAL PLATED GOLD FLASH SOLDER TYPE	1SET
6	MICRO USB B CONNECTOR OVERMOULD 40P/PVC	G
7	MICRO USB B CONNECTOR INNERMOULD PE	1SET

CONNECTIONS		
P1	COLOR	P2
1	BLUE	1
2	WHITE	3
3	GRAY	2
5	GREEN	4+5

	PART NO. DBMIB-5B09-M1F		TOLERANCES ARE .X ± .XX ± .XXX ± AWG	DESCRIP TION:	AREA	REVISIONS	HK	DATE
	DWG NO. DBMIB-5B09-M1F							
	FILE NO.		DRAWING BY					
	UNIT / mm	SCALE 1:1	PROJECTION					