



DBMPVUB-09084A-A1M-LF
LEADFREE

PIN OUT:

P1	P2	P3
1	7	
2	6	
3	5	
5	4	4
7	8	
	1	1
	2	2
	3	3
shell		shell

RoHS Compliant

ITEM	PART NO.	DESCRIPTION	REMARK
1	5501-09SA-02-03-F1	D-SUB STANDARD SOLDER TYPE 9WAYS FEMALE WHITE	1
2	5075A-02-02-F1	USB A MALE INSULATOR WHITE MOLDING TYPE	1
3	2026A-08-F4	2.0MM SINGLE ROW HOUSING	1
4	2226TG	2.0MM HOUSING HALF GOLD TERMINAL	8
5	810A-8C28A5.0BK	UL2464 28AWG *8C+AE OD:5.0MM COLOR BLACK	
6	810B-1P2C2824B4.7BK	UL 2725 28AWG*1P+24AWG*2C+AEB COLOR BLACK	
7	808-4*36A	SCREW #4-40UNC L=36.5MM	2
8	827-PVC-50P-BK	PVC MOLDING 50P COLOR BLACK	

 煜倫股份有限公司	PART NO. DBMPVUB-09084A-A1M		CHECKED BY CY DRAWING BY PROJECTION	TOLERANCES ARE .X ± 0.2 .XX ± .XXX ± AWG	DESCRIP TION:			
	UNIT / mm	SCALE 1:1			AREA	REVISIONS	HK	DATE