



WIRING DIAGRAM

| P1 | P3 | P2 | P3 |
|----|----|----|----|
| 1 | 1 | 1 | 11 |
| 2 | 3 | 2 | 13 |
| 3 | 5 | 3 | 15 |
| 4 | 7 | 4 | 17 |
| 5 | 9 | 5 | 19 |
| 6 | 2 | 6 | 12 |
| 7 | 4 | 7 | 14 |
| 8 | 6 | 8 | 16 |
| 9 | 8 | 9 | 18 |

RoHS Compliant

| 4 | CONN. | 2 | PCS | DB9P M CRIMPING |
|-----|----------|------|-------|------------------------|
| 3 | TERMINAL | 18 | PCS | DP2.0-GP |
| 2 | HOUSING | 1 | PCS | DP2.0-2*10PH |
| 1 | CABLE | 18 | PCS | UL1007 28AWG 200*4*2mm |
| NO. | PART NO. | Q'TY | UNITS | DESCRIPTION |



PART NO. DBMPVX21-09B10-EN20C

DWG NO. DBMPVX21-09B10-EN20C

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE
.X ± 0.2
.XX ±
.XXX ±
AWG

| DESCRIP TION: | AREA | REVISIONS | HK | DATE |
|---------------------------|------|-----------|----|------|
| DB9M*2/DP2.0-2*10PH/200mm | | | | |

焯倫股份有限公司