



ELECTRONIC TEST:

1. Voltage:DC 300V 10M ohm/10 ms.
2. Contact resistance: 3.0 ohm MAX.
3. 100% Open,Short,Mis-Wire Testing.

PIN ASSIGNMENT

P1	P2
1	5
2	4
3	6
4	7
5	14
6	10
7	2
8	15
9	16

ITEM	DESCRIPTION	Q'TY	REMARK
5	PVC: BLACK OVERMOLD,45P	45G	
4	SCREW ; F24#, L=24MM, BLACK HANDLE	2PCS	
3	CONN:OBD-II 16P MALE,PINS NICKEL,BLACK INSUTIONLA,REV:USA	1PCS	
2	CONN: D-SUB 9P FEMALE,BLUE INSULATION	1PCS	
1	UL2464 26AWG*9C+AL,OD=6.0MM,PVC BLACK.	1PCS	

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY
CHECKED BY GENIUS
UNIT / mm SCALE 1:1
DATE
SIZE A4

X.±
.X±
.XX±
.XXX±
ANG ±

PJECTION

照片框

ORDER INFORMATION

DBOBD2-091626-A1M5-LF

SERIES

LEADFREE
1500mm
FEMALE TO MALE
26 AWG
09 TO 16 WAY

DESCRIPTION: OBD-II 16P M TO DB9P FEMALE