



PIN OUT

DB25F	RJ45	AC ADAPTOR
2	3	
6	4	
4		
5		
20	5	
7	6	
	7	+(120VAC 60Hz)
	8	-(24VDC 200mA)

RoHS Compliant

	PART NO. DBRJACFP-258802-A6F		TOLERANCES ARE .X ± 0.2 .XX ± .XXX ± AWG	DESCRIPTION: D-SUB 25PIN FEMALE TO RJ45 PLUG AND AC ADAPTOR				
	DWG NO. DBRJACFP-258802-A6F							CHECKED BY CY
焯倫股份有限公司	FILE NO.		DRAWING BY		AREA	REVISIONS	HK	DATE
	UNIT / mm	SCALE 1:1	PROJECTION					

J
I
H
G
F
E
D
C
B
A

****CONSTRUCTION:**

- CABLE (A): * UTP (4PR/24#) OD:5.1mm BEIGE PVC JACKET.
- CABLE (B): * NO UL (1C/24#)*2 OD:1.4*2.8mm.

****CONNECTORS:**

- 1.DB25F:
 - * D-SUB 25PIN FEMALE SOLDER TYPE.
 - * PINS: PHOSPHOR BRONZE WITH GOLD PLATED.
 - * SHELL: STEEL WITH NICKEL PLATED.
 - * INSULATOR: WHITE COLOR P.B.T UL 94V-0 RATED.
 - * SCREW: THUMBSCREW #4-40 UNC BEIGE COLOR.
 - * MOLDED: BEIGE PVC 45P.
- 2.RJ45 PLUG:
 - * RJ45 8P8C PLUG.
 - * PINS: PHOSPHOR BRONZE WITH GOLD PLATED 50 MICRON.
 - * INSULATOR: CLEAN PC INSULATOR.
 - * MOLDED: BEIGE PVC 60P.
- 3.AC ADAPTOR: * INPUT:120VAC 60Hz OUTPUT:24VDC 200mA
- 4.LABEL: * PRINT: "POWER HARNESS POWER-NR0001"
- 5.TEST: * CT:2 Ohm IS:5M ohm.
- 6.PACKING: * PACKED EACH CABLE IN A POLY BAG.
- 7.MATERIAL: * MATERIAL WITH RoHS GRADE.



煜倫股份有限公司

PART NO. DBRJACFP-258802-A6F		CHECKED BY CY	TOLERANCES ARE .X ± 0.2 .XX ± .XXX ± AWG	DESCRIPTION:			
DWG NO. DBRJACFP-258802-A6F							
FILE NO.		DRAWING BY	PROJECTION	AREA	REVISIONS	HK	DATE
UNIT / mm	SCALE 1:1						