



PIN OUT

DB25F	RJ45	DC JACK
2	3	
6	4	
4		
5		
20	5	
7	6	
	7	PIN
	8	SHELL

MORETHANALL
CONNECTORS
ASSEMBLIES

煜倫股份有限公司

PART NO. DBRJDCJ-258821-A6F
DWG NO. DBRJDCJ-258821-A6F
FILE NO.
UNIT / mm SCALE 1:1

CHECKED BY CY
DRAWING BY
PROJECTION

TOLERANCES ARE
.X ± 0.2
.XX ±
.XXX ±
AWG

RoHS Compliant

DESCRIPTION:	D-SUB 25PIN FEMALE TO RJ45 PLUG AND DC JACK			
AREA	REVISIONS	HK	DATE	

****CONSTRUCTION:**

- CABLE (A): * UL2464 (6C/26#)+EA OD:5.2mm BLACK JACKET.
- CABLE (B): * UL2464(2C/26#) OD:3.5mm BLACK JACKET.

****CONNECTORS:**

- 1.DB25F: * D-SUB 25PIN FEMALE SOLDER TYPE.
 * PINS: PHOSPHOR BRONZE WITH GOLD PLATED OVER NICKEL.
 * SHELL: STEEL WITH NICKEL PLATED.
 * INSULATOR: WHITE COLOR P.B.T UL 94V-0 RATED.
 * SCREW: THUMBSCREW #4-40 UNC BEIGE COLOR.
 * MOLDED: BLACK PVC 45P.
- 2.RJ45 PLUG: * RJ45 8P8C PLUG.
 * PINS:PHOSPHOR BRONZE WITH GOLD PLATED 50 MICRON.
 * INSULATOR: CLEAN PC INSULATOR.
 * MOLDED: GRAY PVC 60P.
- 3.DC JACK: * DC 5.5*2.1mm JACK SOLDER TYPE.
 * BRASS WITH NICKEL PLATED.
 * INSULATOR: BLACK ABS.
 * MOLDED: BLACK PVC 45P.
- 4.TEST: * CT:2 Ohm IS:5M ohm.
- 5.PACKING: * PACKED EACH CABLE IN A POLY BAG.
- 6.MATERIAL: * MATERIAL WITH RoHS GRADE.



PART NO. DBRJDCJ-258821-A6F		CHECKED BY CY		TOLERANCES ARE .X ± 0.2 .XX ± .XXX ± AWG	DESCRIPTION:			
DWG NO. DBRJDCJ-258821-A6F		DRAWING BY						
FILE NO.		PROJECTION		AREA	REVISIONS	HK	DATE	
UNIT / mm	SCALE 1:1							

煜倫股份有限公司