



PIN OUT:

P1	P2
A	1
P	2
S	14
R	3
T	16
C	4
D	5
E	6
H	20
B	7
F	8
Y	15
AA	12
V	17
X	9
L	18
N	21
J	22
U	24
W	11
NN	25

NO.	ITEM	DESCRIPTION	Q'TY
1	V.35-F	V.35 FEMALE & ASSEMBLY HOOD	1&1SET
2	5501-25PA-02-F1	D-SUB 25 MALE INSULATION WHITE SOLDER TYPE	1
3	810A-21C24B9.0BK	UL 2464 24AWG*21C+AEB OD:9.0MM COLOR BLACK	
4	827-PVC-50P-BK	PVC MOLDING 50P COLOR BLACK	
5	808-4.0*45B	SCREW #4*40UNC L=45MM	2

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ±

.X ±

.XX ±

.XXX ±

ANG ±

PPOJECTION

照片框

ORDER INFORMATION

DBV35-253424-E3M-LF

SERIES

LEADFREE

3000mm

MALE TO FEMALE

24 AWG

25 TO 34 WAY

DESCRIPTION: V.35 F TO DB25 M CABLE ASS'Y